



This all-in-one long range UHF Gen 2 reader/writer is designed for industrial environment.

This long range UHF Gen 2 reader/writer operates in a frequency range from 860MHz to 960MHz. It is compatible with both EPC Class 1 Gen 1 and Gen 2 protocols. This reader/writer has a read/write distance of up to 15m. Its RF power output is from 0dB to 30Db. Developers can find that the reader/writer is an excellent tool for testing and validating applications because they can develop customer specific features based on the FREE SDK that is shipped with the RFID reader/writer.

Key features

- ✓ Antenna compatibility: built-in antenna(12dBi)
- ✓ Antenna connection: none
- ✓ Power requirement: DC + 9V (<3A)
- ✓ Transponder compatibility: EPC Class 1 Gen 1 and Gen 2
- ✓ I/O interface: one digital in





Technical Specifications

Frequency	860MHz to 960MHZ
RF power output	0dB to 30Db (adjustable though software)
Communication interface	RS232, RS485, Wiegand26/34 (RJ45 Ethernet interface is optional)
Read/write distance	Up to 15m (tag dependent)
Technical certificates	CE, FCC
Dimensions	460mm x 460mm x 50mm
Housing	ABS
Operating temperature	-10°C to 55°C
Storage temperature	-20°C to 85°C
Humidity	5% to 80% non-condensing





GAO RFID Inc.

A Member of GAO Group

Celebrating Over 15 Year of Innovation

Product Overview

Long Range UHF Gen 2 Reader/Writer (216010)



GAO Group

Celebrating Over 15 Years of Innovation

GAORFID.com

GAOTek.com

GAORFIDAssetTracking.com

GAOComm.com

GAOInstruments.com

GAOFiberOptics.com

GAOEmbedded.com

GAOResearch.com

Toll Free (USA & Canada)

1-877-585-9555

All Other Areas

416-292-0038

Dial Ext.601 for Sales
Ext.602 for Other Inquiries

China: 86-519-80691090
86-519-80691089

sales@GAORFID.com