



This flexible, handheld computer terminal is an ideal choice as an RFID Reader and has been proven successful in a number of applications including asset tracking, livestock tracking, warehousing and manufacturing.

This reader offers the Bluetooth enabled in both full keyboard and short keypad varieties with an option of either Microsoft Embedded CE 5.0 or Windows Mobile 6 classic operating systems. The inclusion of an SDK and a number of configuration options brings complete flexibility to meet the specific needs for countless solutions. Additionally, with its own shock and vibration resistant design, it is able to work even in harsh environment.



Key Features

- ✓ Bluetooth enabled
- ✓ Shock and vibration resistant
- ✓ Dust and water resistant

Specifications

Power Requirements	9 V DC/120 V AC 300 mA
Interface	RS232
Baud Rate	2400 bps to 19200 bps 8,N,1 No Flow Control
Data Structure	STX, ETX selectable
Frequency	125 kHz
Read Distance	0 cm to 10 cm
Transponders Supported	Output data read length has no limit
Technical Certificates	FCC
Dimensions	134.2 mm × 65.4 mm × 38.4 mm
Weight	25 g
Operating Temperature	0 °C to 55 °C
Storage Temperature	-25 °C to 65 °C
Humidity	5% to 95% relative



GAO RFID Inc.

A Member of GAO Group

Celebrating Over 15 Year of Innovation

Product Overview

Rugged Handheld Terminal RFID Reader (246005)



GAO Group

GAORFID.com

GAOTek.com

GAORFIDAssetTracking.com

GAOComm.com

GAOInstruments.com

GAOFiberOptics.com

GAOEmbedded.com

GAOResearch.com

Toll Free (USA & Canada)

1-877-585-9555

All Other Areas

416-292-0038

Dial Ext.601 for Sales
Ext.602 for Other Inquiries

sales@GAORFID.com