



***This low profile metal mount tag is an optimal choice for fixed asset tracking and mobile asset tracking.***

This durable universal RFID asset tag is an ideal tool for tracking metal IT assets. Its thin design offers the lowest profile in its class which makes it unobtrusive. The revolutionary tag uses an inlay design and passive RFID technology to obtain excellent read range on a variety of surfaces such as metal, plastic, and wood. Moreover, the inlay adheres to a durable label with subsurface printing that protects the bar code, logo and other information from harsh chemicals and abrasion.

**Application**

✓ Fixed asset tracking

✓ Mobile asset tracking





**Technical Specifications**

Operating Frequency	915 MHz
Sizes	27/8" x 13/8"
Read Range	15+ feet
Construction	0.002" thick polypropylene or polyester label adhered to proprietary inlay wrapped around 1/16" closed cell foam. Total product thickness is 0.085"
Operating Temperature	0 °F to 175 °F
RF Protocol	ISO/IEC 18000-6C, EPC Class 1 Gen 2
RoHS	2002/95/EC Compliant



**GAO Group**

- [GAORFID.com](http://GAORFID.com)
- [GAOTek.com](http://GAOTek.com)
- [GAORFIDAssetTracking.com](http://GAORFIDAssetTracking.com)
- [GAOComm.com](http://GAOComm.com)
- [GAOInstruments.com](http://GAOInstruments.com)
- [GAOFiberOptics.com](http://GAOFiberOptics.com)
- [GAOEmbedded.com](http://GAOEmbedded.com)
- [GAOResearch.com](http://GAOResearch.com)

Toll Free (USA & Canada)

**1-877-585-9555**

All Other Areas

**416-292-0038**

Dial Ext.601 for Sales  
Ext.602 for Other Inquiries

[sales@GAORFID.com](mailto:sales@GAORFID.com)