

***The high performance UHF RFID tag provides a long read range of up to 7 meters on metal and 3.5 meters in metal.***

This UHF RFID tag is compliant with EPC class 1 Gen 2 and ISO18000-6C protocols and offers a long read range of up to 7 meters on metal and 3.5 meters in metal reader dependent.



### **Key Features**

- ✓ Compact size, light weight
- ✓ Provides long read range of up to 7 meters on metal and 3.5 meters in metal
- ✓ Provides 400 tags per second read rate for 96-EPC bit number
- ✓ IP68 housing
- ✓ Compliant with EPC class 1 Gen 2 and ISO18000-6C protocols

## Technical Specifications

Protocol	EPC C1G2 (ISO18000-6C)
Operating Frequency	902 MHz to 928 MHz (US); 866 MHz to 868 MHz (EU)
IC Type	Alien H3
Memory	512 bit user memory; 64 bit TID; 96 bit EPC
Read Rate	400 tags per second for 96 EPC bit number
Write Cycles	100000 at 25 °C
Data Retention	50 years
Operation Temperature	-40 °C to 85 °C
Application Temperature	-40 °C to 150 °C
IP Rate	IP 68
Attachment	Adhesive
Size (L × W × H)	25 × 9 × 3 mm
Weight	3.6 g
Avg. <a href="#">read range</a> on metal, 4W EIRP	7.0 m
Avg. <a href="#">read range</a> in metal, 4W EIRP	3.5 m

<p><b>GAO Group</b></p> <p><a href="http://GAORFID.com">GAORFID.com</a></p> <p><a href="http://GAOTek.com">GAOTek.com</a></p> <p><a href="http://GAOResearch.com">GAOResearch.com</a></p>	<p>Toll Free (USA &amp; Canada)</p> <p><b>1-877-585-9555</b></p> <p>All Other Areas</p> <p>416-292-0038</p> <p>Dial Ext.601 for Sales Ext.602 for Other Inquiries</p> <p><a href="mailto:sales@GAORFID.com">sales@GAORFID.com</a></p>
---	---